

## Air Hose and Welding Hose

**PVC Air Hose - Heavy Duty** Virgin polyvinylchloride jacket is abrasion and oil resistant, polyester yarn reinforced, working temperature range: 0°F to 140°F, solid brass male fittings

Item No.	Diameter	Length	Fittings	Color	Maximum Pressure		Pallet Pack
					Working	Burst	
ATAH-38025	3/8"/10mm	25Ft/7.57M	1/4" NPT	Blue	300 PSI	1200 PSI	360
ATAH-38050	3/8"/10mm	50Ft/15.15M	1/4" NPT	Blue	300 PSI	1200 PSI	240
ATAH-38100	3/8"/10mm	100Ft/30.3M	1/4" NPT	Blue	300 PSI	1200 PSI	120



**Rubber Air Hose - Industrial Duty** 3 Ply construction begins with a nitrile synthetic rubber tube reinforced with **Xtremesh™** yarn and covered with a EPDM rubber which is highly oil resistant, working temperature range: -20°F to 140°F, solid brass male fittings

Item No.	Diameter	Length	Fittings	Color	Maximum Pressure		Pallet Pack
					Working	Burst	
ATAH-38025R	3/8"/10mm	25Ft/7.57M	1/4" NPT	Yellow	300 PSI	1200 PSI	360
ATAH-38050R	3/8"/10mm	50Ft/15.15M	1/4" NPT	Yellow	300 PSI	1200 PSI	240
ATAH-38100R	3/8"/10mm	100Ft/30.3M	1/4" NPT	Yellow	300 PSI	1200 PSI	120
ATAH-12050R	1/2"/12mm	50Ft/15.15M	3/8" NPT	Red	300 PSI	1200 PSI	160
ATAH-12100R	1/2"/12mm	100Ft/30.3M	3/8" NPT	Red	300 PSI	1200 PSI	80



3/8"/10mm



1/2"/12mm

**Roofing Air Hose - Industrial Duty** 3 Ply construction begins with a nitrile synthetic rubber tube reinforced with **Xtremesh™** yarn and covered with a EPDM rubber which is highly oil resistant, working temperature range: -20°F to 140°F, solid brass male fittings, made specifically for the construction/roofing industry where light weight is paired with heavy duty

Item No.	Diameter	Length	Fittings	Color	Maximum Pressure		Pallet Pack
					Working	Burst	
ATAH-14050R	1/4"/6.35mm	50Ft/15.15M	1/4" NPT	Red	300 PSI	1200 PSI	360
ATAH-14100R	1/4"/6.35mm	100Ft/30.3M	1/4" NPT	Red	300 PSI	1200 PSI	240



1/4"/6.35mm

**Flexx™ Air Hose - Extreme Duty** thermoplastic compound jacket provides flexibility in extreme low temperature conditions of up to -40°F, internal rubber tube reinforced with **Xtremesh™** yarn, working temperature range -40°F to 140°F, solid brass male fittings, hi viz black bend restrictors

Item No.	Diameter	Length	Fittings	Color	Maximum Pressure		Pallet Pack
					Working	Burst	
ATAH-38025T	3/8"/10mm	25Ft/7.57M	1/4" NPT	Orange	300 PSI	1200 PSI	360
ATAH-38050T	3/8"/10mm	50Ft/15.15M	1/4" NPT	Orange	300 PSI	1200 PSI	240
ATAH-38100T	3/8"/10mm	100Ft/30.3M	1/4" NPT	Orange	300 PSI	1200 PSI	120



3/8"/10mm

**Manual Air Hose Reel** made from heavy gauge steel, will hold up to 100 feet of 3/8" diameter hose or 50 feet of 1/2" diameter hose, manual return, mounts anywhere

Item No.	Description	Fittings	Case Pack
ATAHRR-001	Manual Return Air Hose Storage Reel	1/4" NPT	4



Valley Industries Corporation,

Tel: (562) 633-9418

Fax: (562) 633-9412

7500 Jefferson Street, Paramount, CA 90723, USA





## Air Hose and Welding Hose


**Retractable Air Hose Reels** are spring rewind reels made from solid steel axles and mounting bases, reels come with **Valley®** industrial duty rubber air hoses, whip hose, and hose stop guard, smooth operating roller bearings for long life, solid brass fittings

Item No.	Description	Fittings	Working	Burst	Pallet Pack
ATAHRR-025	25 Ft. x 3/8" Retractable Air Hose Reel	1/4" NPT	300 PSI	1200 PSI	60
ATAHRR-050	50 Ft. x 3/8" Retractable Air Hose Reel	1/4" NPT	300 PSI	1200 PSI	40
ATAHRR-050A	50 Ft. x 1/2" Retractable Air Hose Reel	3/8" NPT	300 PSI	1200 PSI	40



**Retractable Twin-Line Welding Hose Reels** are spring rewind reels made from solid steel axles and mounting bases, reels come with **Valley®** industrial duty rubber twin-line welding hoses, whip hose, and hose stop guard, smooth operating roller bearings for long life, solid brass fittings

Item No.	Description	Fittings	Working	Burst	Pallet Pack
ATWHRR-025	25 Ft. x 1/4" Retractable Weld Hose Reel	1/4" NPT	250 PSI	750 PSI	40
ATWHRR-050	50 Ft. x 1/4" Retractable Weld Hose Reel	1/4" NPT	250 PSI	750 PSI	40



**Twin-Line Welding Hose - Industrial Duty** 3 Ply construction begins with a nitrile synthetic rubber tube reinforced with **Xtremesh™** yarn and covered with a EPDM rubber which is highly oil and UV resistant, working temperature range: -20°F to 140°F, solid brass female NPT fittings, designed for oxy/acetylene welding kits, twin-line green and red hoses

					Maximum Pressure		
Item No.	Diameter	Length	Fittings	Color	Working	Burst	Pallet Pack
ATWH-14025R	1/4"/6.35mm	25Ft/7.57M	1/4" NPT	GR/RD	250 PSI	750 PSI	180
ATWH-14050R	1/4"/6.35mm	50Ft/15.15M	1/4" NPT	GR/RD	250 PSI	750 PSI	120
ATWH-14100R	1/4"/6.35mm	100Ft/30.3M	1/4" NPT	GR/RD	250 PSI	750 PSI	60



**Recoil Air Hose - Nylon** tubing material resists crimping and bending, self recoiling design is retractable and tangle proof, chemical and corrosion resistant, spring guards, working temperature: 40°F to 140°F, solid brass male fittings

					Maximum Pressure		
Item No.	Diameter	Length	Fittings	Color	Working	Burst	Pallet Pack
ATAHR-1425	1/4"/6.35mm	25Ft/7.57M	1/4" NPT	Yellow	100 PSI	200 PSI	40
ATAHR-1450	1/4"/6.35mm	50Ft/15.15M	1/4" NPT	Yellow	100 PSI	200 PSI	20



**Recoil Air Hose - Polyurethane** tubing material resists crimping and bending, self recoiling design is retractable and tangle proof, chemical and corrosion resistant, spring guards, working temperature: 20°F to 140°F, solid brass male fittings

					Maximum Pressure		
Item No.	Diameter	Length	Fittings	Color	Working	Burst	Pallet Pack
ATAHR-1425P	1/4"/6.35mm	25Ft/7.57M	1/4" NPT	Blue	125 PSI	250 PSI	20
ATAHR-1450P	1/4"/6.35mm	50Ft/15.15M	1/4" NPT	Blue	125 PSI	250 PSI	10
ATAHR-3825P	1/4"/6.35mm	25Ft/7.57M	3/8" NPT	Blue	125 PSI	250 PSI	20
ATAHR-3850P	1/4"/6.35mm	50Ft/15.15M	3/8" NPT	Blue	125 PSI	250 PSI	10



Valley Industries Corporation,

Tel: (562) 633-9418

Fax: (562) 633-9412

7500 Jefferson Street, Paramount, CA 90723, USA